

i9-C



➔ Standalone Fingerprint Time and Attendance Terminal

Fingerprint Templates : 2200
Card Capacity : 2200
Transaction Storage : 1,00,000
Card Reader : Yes
CPU : 32 bit microprocessor 400 MHz
Fingerprint Sensor : 500 DPI Optical Sensor
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : ≤ 1 sec
Algorithm Ver : 10
Display : 2.8" Color TFT
Keypad : 4 x 4 Keypad
LED Indicator : Green/Red
Schedule Bell/Speaker : Mini Speaker
Communication : USB-host , TCP/IP
Push data : Standard
Standard Features : DLST, Automatic Status Switch,
Self Service Query
Power Supply : 5V DC, 2 A
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 213 x 149 x 46

Access Control : Wiegand : NO
Relay : NO / Support Fire Alarm : NO
Door Sensor ; NO / Anti Passback : NO
Door Bell : NO
Exit Readers Support exit readers NO
Battery : NO
Card Readers : NA / Communication : NA
Printer : NA
Compatibility :
External Speaker output available (Optional)
External Bulb output available (Optional)
Compatible Software & SDK :
- Smart office suite desktop and web
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/
ePush server using Push data.
Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP
and Other applications