



**inBio 460**

## ➔ Multidoor Access Control - 4 Door

CPU : 32bit MIPS CPU

RAM : 32MB, Flash Memory : 128MB

Fingerprint Capacity : 3000

Card Capacity : 30,000

Event buffer : 1,00,000

Power / Current : DC 9.6V - 14.4V , Rated Max 1A

Wiegand Reader Port : 4ea (26/34 bit Wiegand ,  
4/8bit for PINRS485)

Reader Port : 1no. extended RS485 Port

Communication : RS485 , TCP/IP

Baud Rate : 38,400bps (recommended) / 9600bps ,  
19,200 bps , 57,600 bps (selectable)

Input Port : 8ea (exit button #1 , exit button #2 ,  
button #3 , button #4,

Door Sensor #1 ,Door Sensor #2 ,

Door Sensor#3 , Door Sensor #4)

Supports : F12 (RS 485) Fingerprint Reader

### Features:

- ▶ 256 time Zones, 256 access levels
- ▶ Anti-passback function
- ▶ Interlock function , Linkage function
- ▶ Multi-Card opening function,  
Remote door opening & closing
- ▶ Real-Time monitoring via web browser
- ▶ Video server integration
- ▶ 4 auxiliary input may be connected to infrared body  
detectors, fire alarms, smoke detectors etc.
- ▶ 4 auxiliary output may be connected to alarms, cameras,  
door bells etc.
- ▶ Supports : eSSL 5000 / 7500 for fingerprint registration

### Connectivity Diagram

